

## Inflatable Shelter



- **Instant**
- **Multi-purpose**
- **Robust**
- **Lightweight**

### **Multiple applications:**

Casualty protection

Medical treatment centre

On-site Command Centre

Decontamination facility

Mess hall

Forensic facilities

Temporary workshop

### **Multiple situations:**

Emergency response

Remote crash site investigation

Working in inhospitable areas

Mountain rescue

Civil defence contingency

Security alerts

Storage

Address:  
15 Moor Road  
Broadstone  
Dorset BH18 8AZ

Telephone:  
+44 (0)1202 657814  
Facsimile:  
+44 (0)1202 693005

Email:  
info@icbrindle.com  
Websites:  
rescueandrecovery.co.uk  
icbrindle.com

# I.C. BRINDLE

## & Co. Ltd



**Working height:** 2.4m at the ridge and 1.8m at the side. **Endurance:** Suitable for sustained use at major incidents

**Robust Construction:** Frame: natural rubber coated polyamide Cover: heavy duty polyurethane coated nylon.

**Transport:** The 4m x 5m unit weighs only 55kg and can be easily carried by two persons. It is easily moved when inflated.

**Inflation:** By a standard breathing air cylinder. Inflation time 40 seconds. Requires no external power source.

**Securing:** Tie-downs and long ground stakes. On a hard surface flaps (optional) provide standing for sand bags, water drums or vehicles.

**Removable Floor:** The floor is attached by Velcro and is easily removed so that the tent may be placed over a vehicle or casualty.

**Ventilation:** Via two upper openings and a screened window. **Service Connections:** A large duct for electric cables and other services.

**Extendable:** Can be connected together. **Door shape:** A range of different shaped doors (subject to the size of the shelter).



internal divisions



lining



detachable floor

	Model 4 x 5	Model 6 x 5	Model 8 x 5
External dimensions (cm)	400 x 500 x 280	600 x 500 x 280	800 x 500 x 280
Internal dimensions (cm)	400 x 460 x 260	600 x 460 x 260	800 x 460 x 260
Inside Height - max / min (cm)	240 / 180	240 / 180	240 / 200
Floor area (sq m)	20	30	40
Air requirements (litres)	1400	1800	2200
Working pressure (bar)	0.25	0.25	0.25
Inflation	1 x 6 litre/300 bar cyl	1 x 6 litre/300 bar cyl	2 x 6 litre/300 bar cyl
Inflation time	40 seconds	40 seconds	40 seconds
Connection	Standard air cylinder		
Weight without / with cylinder	47 / 55 kg	66 / 76 kg	78 / 90 kg
Packed (approx) without / with cyl (cm)	90 x 55 x 40 / 96 x 57 x 43	90 x 60 x 45 / 125 x 42 x 57	90 x 65 x 50 / 130 x 42 x 60

### Included options

- Choice from range of standard colours
- Long ground stakes
- Panel with your name/logo (subject to complexity)
- Choice from range of door shapes (dependant on model)

### Other Options

- Vehicle / Sandbag securing flaps
- Insulated side walls & roof
- Internal divider curtains
- Lighting
- Heating
- Shower cubicle
- Translucent roof

### Special Requirements

The shelter can be adapted to suit different requirements e.g. attaching to command vehicles, etc. If you have a specific need please contact us.