

Helicopter Rescue: Quick-Strop Specifications

Description

Originally designed for the US Coast Guard, the LSC Quick Strop is now available to all rescue activities. Constructed of MIL-SPEC webbing and stainless steel hardware, the Quick Strop provides a quick, safe means of hoisting uninjured personnel. The Strop can be placed under the arms, around the back, or over the head of the survivor in one quick motion. To prevent the survivor from slipping out, a slide buckle is slid down the Strop and attached to an adjustable crotch safety strap which is stored in a zipper pocket on the rear of the Strop. Instructions and pictorials are printed on the Strop.

Approved for use by the US Coast Guard.

Product Specifications

Colour: International orange cover with black webbing.

Weight: 2.54 lbs.

Inspections: Visual prior to each use.
Extended load test (v-ring to v-ring) at 600 lbs every 6 months.

Cleaning: Fresh water rinse with mild detergent.

Materials:

Fabric Cover: 420 denier Nylon.

Pad: 7/16" closed-cell foam.

Main Strap:

(Load Bearing) Type 10 Mil-Spec Nylon Webbing (Breaking Limit 10000 lbs) with TEX 210 Bonded Nylon Thread (Stitch Pattern Breaking Limit 5000 lbs)

Crotch Strap: Type 8 Mil-Spec Nylon Webbing (Breaking Limit 3400 lbs).
Type 13 Mil-Spec Nylon Webbing (Breaking Limit 6000 lbs).

Threads: TEX 45 Bonded Nylon.

TEX 70 Bonded Nylon.

TEX 90 Bonded Nylon.

Zipper: YKK corrosion resistant Vislon® zipper and slider.

Hardware:

Snap Hook: Wichard Stainless Steel Snap Hook, 3-5/32" (Breaking Limit 3750 lbs).

Lifting Eyes: LSC #384 V-Ring with Box, Stainless Steel (Breaking Limit 5200 lbs).

Quick Adjustor: LSC #400 1-3/4" Adaptor Slide, Stainless Steel.

Address:
15 Moor Road
Broadstone
Dorset BH18 8AZ

Telephone:
+44 (0)1202 657814
Facsimile:
+44 (0)1202 693005

Email:
info@icbrindle.com
Websites:
icbrindle.com
rescueandrecovery.co.uk